

Computation of the band structure of two-dimensional Photonic Crystals with hp Finite Elements

K. Schmidt*, P. Kauf

Seminar for Applied Mathematics, ETH Zurich, Rämistrasse 101, 8092 Zürich, Switzerland

Abstract

The band structure of 2D photonic crystals – a periodic material with discontinuous dielectrical properties – and their eigenmodes can be efficiently computed with the finite element method (FEM). For second order elliptic boundary value problems with piecewise analytic coefficients it is known that the solution converges extremely fast, i.e. exponentially, when using p -FEM for smooth and hp -FEM for polygonal interfaces and boundaries. In this article we discretise the variational eigenvalue problems for photonic crystals with smooth and polygonal interfaces in scalar variables with quasi-periodic boundary conditions by means of p - and hp -FEM – this for the transverse electric (TE) and transverse magnetic (TM) modes. Our computations show exponential convergence of the numerical eigenvalues for smooth and polygonal lines of discontinuity of dielectric material properties.

Key words: hp -FEM; exponential convergence; corner singularities; photonic crystals; photonic band structure; quasi-periodic boundary condition

1. Introduction

Photonic crystals are refractive materials with a certain periodic structure in one, two or three directions [1]. The behaviour of light in such media strongly depends on its frequency. At so called “forbidden frequencies” lying in the *band gap* of a particular photonic crystal no wave propagation is possible [2]. Such effects allow for applications in photonics and optics. For manufacturing reasons photonic crystals with two-dimensional periodicity (see figure 1) are very attractive.

Many properties of electrons in semiconductors, which are well explained by quantum mechanics, translate to photonic crystals. Hence, models for the description of photonic crystals are similar to those in solid state physics. For the prediction of photonic crystal properties one relies on a model of an infinite crystal with perfect periodicity. By the Floquet-Bloch transformation [3] the Maxwell eigenvalue problem for the propagating frequencies in an infinite domain is reformulated into a set of eigenvalue problems in the *elementary cell*, parameterised by the quasi-momentum \mathbf{k} . The relation between quasi-momentum and eigen frequencies is the well-known *band structure*.




Fig. 1. A photonic crystal with two-dimensional periodicity.

There is a wide variety of methods to calculate the band structure of photonic crystals [4]. One of the most popular methods is plane waves expansion (PWE) (see e.g. [5,6,1]), which is a Fourier series in the quasi-momentum \mathbf{k} . A pure plane waves approach experiences convergence problems for high-contrast materials, an additional smoothing of the dielectric discontinuities yields only algebraic convergence in the number of expansion coefficients [7]. Other expansion based approaches are the method of Kohn, Korringa and Rostocker (KKR) [8,9], the augmented plane waves expansion [10], which are both restricted to cylindrical structures, or the multiple multipole method (MMP) [11]. Separation of variable approaches are applied for crystals with quadratic veins [12,13]. Furthermore, there are algorithms based on finite differences in time domain (FTDT) [14–16].

* Corresponding author.

Email addresses: kersten.schmidt@math.ethz.ch (K. Schmidt), peter.kauf@sam.math.ethz.ch (P. Kauf).

Unlike the previously mentioned methods, except FTDT, the finite element method [17] uses localised basis functions defined on a mesh. Since the mesh can be unstructured and even curved, the FE method is suitable for resolving complicated geometries. In its h -version, i.e. the mesh width h is decreased, the numerical solutions of elliptic boundary value problems converge algebraically in the number of degrees of freedom (N). With p -FEM [18], [19], where we enrich the trial space with higher order basis functions, *exponential convergence* in N can be obtained, given that boundary and interfaces are smooth and the material coefficients are piecewise analytic. If, additionally, the boundary has corners, the solution is less regular, and a proper combination of mesh size h refinement and element order p enlargement, the hp -FEM [19], [20], is needed to retain exponential convergence. This also holds for curved boundaries [21].

For transmission problems, where there are jumping material coefficients, one expects similar convergence behaviour, especially exponential convergence

- with p -FEM for smooth interfaces,
- with hp -FEM for polygonal interfaces, if the mesh is adaptively refined to the interface corners.

These adaptively refined hp -meshes, which preserve the exponential convergence for polygonal interfaces, are created either based on *a-priori* knowledge or automatically, using *a-posteriori* error estimators. For *a-priori* refinement one marks the interface corners to refine towards them. Thereby so called *geometric meshes* occur, which, by theoretical investigations, are known to provide, together with a linearly increasing polynomial degree away from these corners, exponential convergence. *A-posteriori* error estimators select cells in which the error is large – these cells are then refined or their polynomial degree is increased. Several algorithms can be found in the literature, e.g. [22], [20], [23], and the references therein.

Clearly, due to its exponential convergence the proposed method is asymptotically much more efficient in accuracy and computational effort than widely used FFT based methods like PWM, which converge only algebraically. Furthermore, we use trunk spaces [19], where despite of a reduction of inner degrees of freedom the approximation accuracy stays essentially the same. With these trunk spaces the constant in the exponential convergence is improved compared to the full spaces computations.

Nevertheless, to the knowledge of the authors, no paper discusses those adaptivity results for interface problems with polygonal interfaces, especially not for band structure calculations of photonic crystals. However, we refer to the recent articles on h - and p -FEM for photonic crystals in 2D [24,25] and 3D [26,27].

The objective of this article is to study the convergence of Maxwell eigenvalues of two-dimensional photonic crystals with smooth or polygonal interfaces, respectively, using *a-priori* refinement strategies. We present an algorithm that computes the whole band structure quickly, because the

entries of the system matrices are computed once and then changed only slightly for different \mathbf{k} values.

In chapter 2 we formulate Maxwell's equations, which decouple into two scalar problems for the transverse electric (TE) and transverse magnetic (TM) fields. Then the periodicity in the dielectrical constant will allow us to use the Bloch transform to reformulate the eigenvalue problem on the infinite plane into a family of eigenvalue problems on the elementary cell with quasi-periodic boundary conditions. This family of problems is parametrised by the quasi-momentum \mathbf{k} . We establish weak formulations and discuss the regularity of the resulting eigenfunctions. This regularity is a criterion to choose between different strategies for designing the mesh and distributing the polynomial order to its cells.

In chapter 3 we describe the discretisation of the function spaces by hp finite elements on quadrilateral meshes with curved boundaries and with hanging nodes. First, the spaces with periodic boundaries are built. Then, we cut the basis functions into four parts, which are defined by the multiplication factors coming from the essential quasi-periodic boundary conditions. In the next step we assemble a system matrix for each pair of these parts. The sum of these totally sixteen matrices, each multiplied by the appropriate factor, gives us the overall system matrix for one specific \mathbf{k} value.

We show numerical results in chapter 4. We compute the band structures of different geometries with curved and polygonal interfaces. A comparison to [12] and [13] verifies the results produced by our algorithm. In a convergence analysis we confirm the following expectations:

- The convergence of p -FEM becomes worse if there are interface corners present.
- p -FEM converges only algebraically for geometries with interface corners, whereas hp -FEM recovers exponential convergence in the number of degrees of freedom.

We observe that the discretisation error for p -FEM decreases faster than for hp -FEM up to a certain number of degrees of freedom. This effect is due to the relatively moderate singularities. In these computations we use trunk spaces. We show that their convergence behaviour is better than the one using full tensor-product spaces.

2. Problem formulation

2.1. Scalar equations for TE and TM mode

In three dimensional time-harmonic formulation Maxwell's equations for linear, non-magnetic media, without free charges or free currents, read

$$\operatorname{div} \mathbf{h}(\mathbf{x}) = 0, \quad \operatorname{curl} \mathbf{e}(\mathbf{x}) = -\frac{i\omega}{c} \mathbf{h}(\mathbf{x}), \quad (1a)$$

$$\operatorname{div}(\varepsilon(\mathbf{x}) \mathbf{e}(\mathbf{x})) = 0, \quad \operatorname{curl} \mathbf{h}(\mathbf{x}) = \frac{i\omega}{c} \varepsilon(\mathbf{x}) \mathbf{e}(\mathbf{x}), \quad (1b)$$

with $\mathbf{e}(\mathbf{x})$ and $\mathbf{h}(\mathbf{x})$ being the electric and magnetic field, respectively, ω the angular frequency, c the vacuum speed of

light, $\varepsilon(\mathbf{x})$ the frequency-independent (relative) dielectrical constant. We assume lossless media, so $\varepsilon(\mathbf{x})$ is real. The dielectrical constant is bounded from below by 1 and from above by a positive constant $\varepsilon_{\max} < \infty$.

Together with the two constraint equations and a suitable decay condition for $|\mathbf{x}| \rightarrow \infty$, decoupling equations (1) leads to two equivalent eigenvalue problems

$$\operatorname{curl} \operatorname{curl} \mathbf{e}(\mathbf{x}) = \left(\frac{\omega}{c}\right)^2 \varepsilon(\mathbf{x}) \mathbf{e}(\mathbf{x}), \quad (2a)$$

$$\operatorname{curl} \left(\frac{1}{\varepsilon(\mathbf{x})} \operatorname{curl} \mathbf{h}(\mathbf{x}) \right) = \left(\frac{\omega}{c}\right)^2 \mathbf{h}(\mathbf{x}), \quad (2b)$$

i.e. they yield the same spectrum.

Since we consider the 2D case, i.e. there is only propagation in the (x_1, x_2) -plane – the plane of periodicity – but not perpendicular to it, the fields do not vary along the x_3 -direction. Thus, we can split the electromagnetic fields in (2) into the transverse electric (TE) mode with $h^1 = h^2 = e^3 = 0$ and the transverse magnetic (TM) mode with $e^1 = e^2 = h^3 = 0$. Each mode yields a scalar and a vector valued problem. Because both, scalar and vector valued formulations, lead to the same spectrum, it is sufficient to consider the scalar problems for TE and TM modes, which are Helmholtz like problems

$$-\operatorname{div} \operatorname{grad} e(\mathbf{x}) = \left(\frac{\omega}{c}\right)^2 \varepsilon(\mathbf{x}) e(\mathbf{x}), \quad (3\text{-TM})$$

$$-\operatorname{div} \left(\frac{1}{\varepsilon(\mathbf{x})} \operatorname{grad} h(\mathbf{x}) \right) = \left(\frac{\omega}{c}\right)^2 h(\mathbf{x}). \quad (3\text{-TE})$$

The eigenfunctions of (3) fulfil the Neumann transmission condition

$$\left[\partial_{\mathbf{n}} e(\mathbf{x}) \right] = \left[\frac{1}{\varepsilon(\mathbf{x})} \partial_{\mathbf{n}} h(\mathbf{x}) \right] = 0, \quad (4)$$

where $[u]$ denotes the jump over an arbitrary, piecewise smooth Lipschitz interface $\Gamma \subset \mathbb{R}^2$ with its unit normal vector \mathbf{n} , and $\partial_{\mathbf{n}} u(\mathbf{x}) := \operatorname{grad} u(\mathbf{x}) \cdot \mathbf{n}$.

2.2. The Bloch transformation onto the elementary cell

The photonic crystal is characterised by a periodic dielectrical constant

$$\varepsilon(\mathbf{x} + \mathbf{a}_i) = \varepsilon(\mathbf{x}), \quad i = 1, 2, \quad (5)$$

where the vectors \mathbf{a}_i are the directions of periodicity. They span the fundamental periodicity domain Ω – a parallelogram – which is also called *elementary cell*¹ (see Fig. 2). We regard Ω as a torus, i.e. opposite sides are identified with each other. We call the geometrical sides and corners of Ω Π_i and Γ_i , respectively, with $i \in \{1, \dots, 4\}$, the topological sides γ_1 and γ_2 and the topological corner π (see Fig. 3).

The so called *reciprocal lattice* [28] with periodicity direction $\mathbf{b}_1, \mathbf{b}_2$ fulfilling

$$\mathbf{a}_i \cdot \mathbf{b}_j = 2\pi\delta_{ij}, \quad i, j = 1, 2 \quad (6)$$

¹ Note, that the elementary cell Ω is not uniquely defined by the vectors \mathbf{a}_i .




Fig. 3. The geometrical sides and corners (left) and the topological ones (right) of the torus Ω .

is associated to the photonic crystal. The elementary cell of the reciprocal lattice is the Brillouin zone² B – see Figure 2.

Now, let us define the Floquet-Bloch transform and its inverse [3] by

$$\begin{aligned} \tilde{u}(\mathbf{k}, \mathbf{x}) &= (\mathcal{F}u)(\mathbf{k}, \mathbf{x}) = \frac{1}{|B|} e^{-i\mathbf{k} \cdot \mathbf{x}} \sum_{\mathbf{m} \in \mathbb{Z}^2} u(\mathbf{x} - \mathbf{a}_m) e^{i\mathbf{k} \cdot \mathbf{a}_m}, \\ u(\mathbf{x}) &= (\mathcal{F}^{-1}\tilde{u})(\mathbf{x}) = \int_B e^{i\mathbf{k} \cdot \mathbf{x}} \tilde{u}(\mathbf{k}, \mathbf{x}) d\mathbf{k}, \end{aligned}$$

where $\mathbf{a}_m = m_1 \mathbf{a}_1 + m_2 \mathbf{a}_2$. The Floquet-Bloch transform has the same periodicity as the underlying pattern given by $\varepsilon(\mathbf{x})$, i.e. $\tilde{u}(\mathbf{k}, \mathbf{x} + \mathbf{a}_i) = \tilde{u}(\mathbf{k}, \mathbf{x})$, $i = 1, 2$ for all $\mathbf{x} \in \mathbb{R}^2$.

The Floquet-Bloch transform is an isomorphism between $H^s(\mathbb{R}^2)$ and $H^s(\Omega \times B)$ ($s \in \mathbb{R}_+$) [3], and thus the problems (3) can be transformed onto $\Omega \times B$, with Neumann transmission condition (4) for the jump of $\tilde{e}(\mathbf{x})$ and $\tilde{h}(\mathbf{x})$ over opposite sides of Ω and modified differential operators. The whole spectrum of (2) is the union of the spectra for all $\mathbf{k} \in B$. We can regard $\mathbf{k} \in B$ as a parameter, and obtain a family of eigenvalue problems in Ω .

However, we prefer the slightly different formulation for $e_{\mathbf{k}}(\mathbf{x}) := e^{i\mathbf{k} \cdot \mathbf{x}}(\mathcal{F}e)(\mathbf{x}, \mathbf{k})$ and $h_{\mathbf{k}}(\mathbf{x}) := e^{i\mathbf{k} \cdot \mathbf{x}}(\mathcal{F}h)(\mathbf{x}, \mathbf{k})$

$$-\operatorname{div} \operatorname{grad} e_{\mathbf{k}}(\mathbf{x}) = \left(\frac{\omega}{c}\right)^2 \varepsilon(\mathbf{x}) e_{\mathbf{k}}(\mathbf{x}), \quad (7\text{-TM})$$

$$-\operatorname{div} \left(\frac{1}{\varepsilon(\mathbf{x})} \operatorname{grad} h_{\mathbf{k}}(\mathbf{x}) \right) = \left(\frac{\omega}{c}\right)^2 h_{\mathbf{k}}(\mathbf{x}), \quad (7\text{-TE})$$

with *quasi-periodic* boundary conditions

$$e_{\mathbf{k}}(\mathbf{x} + \mathbf{a}_i) = e^{i\mathbf{k} \cdot \mathbf{a}_i} e_{\mathbf{k}}(\mathbf{x}), \quad (8a)$$

$$h_{\mathbf{k}}(\mathbf{x} + \mathbf{a}_i) = e^{i\mathbf{k} \cdot \mathbf{a}_i} h_{\mathbf{k}}(\mathbf{x}), \quad (8b)$$

and the transmission conditions

$$\partial_{\mathbf{n}} e_{\mathbf{k}}(\mathbf{x} + \mathbf{a}_i) = e^{i\mathbf{k} \cdot \mathbf{a}_i} \partial_{\mathbf{n}} e_{\mathbf{k}}(\mathbf{x}), \quad (9a)$$

$$\frac{1}{\varepsilon(\mathbf{x} + \mathbf{a}_i)} \partial_{\mathbf{n}} h_{\mathbf{k}}(\mathbf{x} + \mathbf{a}_i) = -e^{i\mathbf{k} \cdot \mathbf{a}_i} \frac{1}{\varepsilon(\mathbf{x})} \partial_{\mathbf{n}} h_{\mathbf{k}}(\mathbf{x}), \quad (9b)$$

on $\partial\Omega$ ($i = 1, 2$), with \mathbf{n} the outer normal vector on $\partial\Omega$.

² The fundamental periodicity domain of the reciprocal lattice is not uniquely determined by $\mathbf{b}_1, \mathbf{b}_2$, so we impose the further condition that the Brillouin zone B is the set of all points belonging to a fundamental periodicity domain of the reciprocal lattice, such that $\mathbf{k} \in B$ is closer to 0 than to any other point in the reciprocal lattice.




Fig. 2. The left picture shows a two dimensional setting with periodicity domain Ω . On the right side we see the corresponding Brillouin zone B and the reduced Brillouin zone B_{red} (red triangle).

Furthermore, if the pattern in the elementary cell has additional symmetry, e.g. mirror symmetry w.r.t. the diagonals, the so called reduced Brillouin zone $B_{\text{red}} \subset B$ already contains the whole spectrum (see Fig. 2). A widely used fact is, that in generic cases the band gaps are located at the boundary of B_{red} , therefore the \mathbf{k} -values inside B_{red} can be neglected. In general however this is not true and we need the whole of B_{red} to determine the band gaps [28]. Also for the computation of other quantities such as the density of states or the Wannier functions the whole of B_{red} is needed.

2.3. Weak formulation

For the weak formulation of (7) we take the quasi-periodic boundary conditions (8) as essential and the transmission conditions (9) as natural boundary conditions. Thus, we define the function space

$$H_{\mathbf{k}}^1(\Omega) := \left\{ v \in H^1(\Omega) : v(\mathbf{x} + \mathbf{a}_i) = e^{i\mathbf{k} \cdot \mathbf{a}_i} v(\mathbf{x}) \text{ on } \partial\Omega, i = 1, 2 \right\},$$

and obtain : For all $\mathbf{k} \in B_{\text{red}}$ seek pairs $(h_{\mathbf{k}}, \omega_{\text{TE}})$, $(e_{\mathbf{k}}, \omega_{\text{TM}}) \in H_{\mathbf{k}}^1(\Omega) \times \mathbb{C}$, such that $\forall e'_{\mathbf{k}}, h'_{\mathbf{k}} \in H_{\mathbf{k}}^1(\Omega)$

$$\mathbf{a}_{\text{TM}}(e_{\mathbf{k}}, e'_{\mathbf{k}}) = \left(\frac{\omega_{\text{TM}}}{c}\right)^2 \mathbf{b}_{\text{TM}}(e_{\mathbf{k}}, e'_{\mathbf{k}}), \quad (10\text{-TE})$$

$$\mathbf{a}_{\text{TE}}(h_{\mathbf{k}}, h'_{\mathbf{k}}) = \left(\frac{\omega_{\text{TE}}}{c}\right)^2 \mathbf{b}_{\text{TE}}(h_{\mathbf{k}}, h'_{\mathbf{k}}), \quad (10\text{-TM})$$

with the inner products

$$\mathbf{a}_{\text{TM}}(u, v) = \int_{\Omega} \mathbf{grad} u(\mathbf{x}) \cdot \overline{\mathbf{grad} v(\mathbf{x})} d\Omega, \quad (11\text{a})$$

$$\mathbf{b}_{\text{TM}}(u, v) = \int_{\Omega} \varepsilon(\mathbf{x}) u(\mathbf{x}) \overline{v(\mathbf{x})} d\Omega, \quad (11\text{b})$$

$$\mathbf{a}_{\text{TE}}(u, v) = \int_{\Omega} \frac{1}{\varepsilon(\mathbf{x})} \mathbf{grad} u(\mathbf{x}) \cdot \overline{\mathbf{grad} v(\mathbf{x})} d\Omega, \quad (11\text{c})$$

$$\mathbf{b}_{\text{TE}}(u, v) = \int_{\Omega} u(\mathbf{x}) \overline{v(\mathbf{x})} d\Omega, \quad (11\text{d})$$

where \overline{v} is the complex conjugate of v .

The boundary terms from partial integration vanish due to the boundary conditions and cancellation of the factors $e^{i\mathbf{k} \cdot \mathbf{a}_i}$ with their complex conjugates.

Lemma 2.1 *The eigenvalues ω_{TM} and ω_{TE} of (10) are real.*

PROOF. Out of hermiticity in (11) it follows that all the eigenvalues $\left(\frac{\omega}{c}\right)^2 \in \mathbb{R}$. By choosing $e_{\mathbf{k}} = e'_{\mathbf{k}}$ and $h_{\mathbf{k}} = h'_{\mathbf{k}}$ in equation (10) we also get that $\left(\frac{\omega}{c}\right)^2 \geq 0$, implying $\omega \in \mathbb{R}$.

Lemma 2.2 *Zero eigenvalues in (10) only occur if $\mathbf{k} = 0$.*

PROOF. We introduce the space $H_{\mathbf{k}, \infty} = H_{\mathbf{k}}^1(\Omega) \cap C^\infty(\Omega)$, which is dense in $H_{\mathbf{k}}^1(\Omega)$. If $\omega = 0$, then $a_{\text{TE}}(h_{\mathbf{k}}, h_{\mathbf{k}}) = 0$, which is the case only if $h_{\mathbf{k}} = \text{const}$. If $\mathbf{k} \neq 0$, the only constant function in $H_{\mathbf{k}, \infty}$ is 0, but 0 is not an eigenfunction, which proves the lemma.

2.4. Regularity of eigenfunctions

The regularity of the eigenfunctions $e_{\mathbf{k}}(\mathbf{x})$ or $h_{\mathbf{k}}(\mathbf{x})$ of (7) determines the accuracy of their representation in discrete trial spaces and determines which adaptive refinement strategy is optimal.

To analyse this regularity we look at the subdomains $\Omega_i \subset \Omega$, in which the dielectrical constant $\varepsilon(\mathbf{x})$ and also $\frac{1}{\varepsilon(\mathbf{x})}$ are analytic.

$$\varepsilon(\mathbf{x})|_{\Omega_i} \in \mathcal{A}(\Omega_i)$$

W.l.o.g. we assume that the elementary cell Ω is composed into two such domains Ω_1 and Ω_2 , i.e.

$$\overline{\Omega} = \overline{\Omega_1} \cup \overline{\Omega_2}.$$

Their interface, assumed to be Lipschitz, is designated by $\Gamma := \partial\Omega_1 \cap \partial\Omega_2$. We consider a piecewise analytic interface Γ . There can be non-analytic points, i.e. there is no parametrisation around such points, for which arbitrarily high derivatives exist. We call these points *corners*, and the set of interface corners \mathfrak{C} .

2.4.1. Smooth interface

Let the interface be smooth, i.e. $\mathfrak{C} = \emptyset$. Then the eigenfunctions $e_{\mathbf{k}}(\mathbf{x})$ or $h_{\mathbf{k}}(\mathbf{x})$ of (7) are expected to be analytic in each subdomain up to the interface, i.e.

$$e_{\mathbf{k}}(\mathbf{x})|_{\overline{\Omega_i}} \in \mathcal{A}(\overline{\Omega_i}), \quad h_{\mathbf{k}}(\mathbf{x})|_{\overline{\Omega_i}} \in \mathcal{A}(\overline{\Omega_i}), \quad i = \{1, 2\}.$$

Just on the interface Γ there is a kink, but no singularity.

2.4.2. Polygonal interface

Now, let the interface contain corners. Then we can expect the eigenfunctions $e_{\mathbf{k}}(\mathbf{x})$ or $h_{\mathbf{k}}(\mathbf{x})$ to be analytic in each domain up to the interface corners \mathfrak{C} , i.e. for $i = \{1, 2\}$

$$e_{\mathbf{k}}(\mathbf{x})|_{\overline{\Omega_i} \setminus \mathfrak{C}} \in \mathcal{A}(\overline{\Omega_i} \setminus \mathfrak{C}), \quad h_{\mathbf{k}}(\mathbf{x})|_{\overline{\Omega_i} \setminus \mathfrak{C}} \in \mathcal{A}(\overline{\Omega_i} \setminus \mathfrak{C}).$$

At the material corners \mathfrak{C} there is a singularity, i.e. there is a (higher order) derivative, which is not in $L^2(\Omega)$. The strength of the singularity at a corner $\mathcal{C} \in \mathfrak{C}$ depends on the surrounding dielectrical constant and on the opening angle.

A technique to determine the singularity at \mathcal{C} for the TE mode for straight material edges is to solve a local boundary value problem³

$$-\operatorname{div}\left(\frac{1}{\varepsilon(\mathbf{x})} \operatorname{grad} h_{\mathbf{k}}(\mathbf{x})\right) = 0$$

in polar coordinates in the neighbourhood of \mathcal{C} (see e.g. [29]). This problem has a solution of the form $r^\lambda s(\phi)$. A more sophisticated technique to obtain the singularity functions, based on the Kondrat'ev method, is described in [30] for the 3D case. There, the techniques used for edge singularities are applicable for the point singularities in the 2D case.

2.5. Mesh design principles

For smooth interfaces the eigenfunctions are piecewise analytic. In the case where the interface is exactly resolved by element boundaries, it is well known [19], that p -FEM on a fixed mesh shows exponential convergence of eigenfunctions and eigenvalues in N

$$|\lambda - \lambda_N| \leq C \exp(-\beta N^{1/3}). \quad (12)$$

For polygonal interfaces the eigenfunctions are analytic up to the material corners and the singular functions are in the class of weighted spaces $B_\beta^2(\Omega)$ [31,32]. It is well known from hp theory [31,32,19], that in the case where the interface is exactly resolved by element boundaries and hp adaptive spaces are used, i.e. a-priori the mesh is refined towards the material corners \mathfrak{C} and the polynomial degree is raised linearly away from \mathfrak{C} , the eigenfunctions are approximated with exponential convergence (12).

3. Algorithm

The finite elements are based on geometric meshes \mathcal{M} on the periodic domain Ω , whose construction is explained

³ We expect the singularity to be the same for all \mathbf{k} .

in section 3.1. In section 3.2 the basis functions, which span the periodic hp -adaptive finite element space on \mathcal{M} are described. Each of these basis functions $b(\mathbf{x})$ is cut into the four parts $b^0(\mathbf{x}), \dots, b^3(\mathbf{x})$. Linear combinations of these parts with phase factors define an associated quasi-periodic basis function (Sec. 3.3). The system matrices of the discrete eigenvalue problem for each quasi-momentum \mathbf{k} are constructed as a linear combination of phase factors and system matrices \mathbf{A}^{mn} , which are built out of combinations of the basis function parts $b^m(\mathbf{x})$ and $b^n(\mathbf{x})$ (Sec. 3.4).

3.1. Geometric meshes

The periodicity cell Ω is covered by a conforming quadrilateral mesh \mathcal{M}_0 with curvilinear quadrilateral cells, that resolves the material interfaces. Thus, material corners \mathfrak{C} are cell nodes and material interfaces \mathbb{I} are represented by curved edges. Each cell is described by an element mapping F_K from the reference cell $[0, 1]^2$, which is constructed by Blending techniques [33].

As written in section 2.2, we regard Ω as a torus, i.e. opposite sides are identified with each other. To ensure this identification also for the mesh \mathcal{M}_0 , opposite sides of Ω have the same subdivision into edges and opposite edges are topologically identical, as well as all the corners of Ω (see Fig. 3).

The coarse mesh \mathcal{M}_0 is the root of a family of meshes $\mathbb{M} = \{\mathcal{M}_i\}, i \in \mathbb{N}_0$. New entities, i.e. cells, edges and vertices, accrue in \mathcal{M}_1 by refining \mathcal{M}_0 geometrically towards the material corners. Thus, we subdivide those cells which touch a material corner $\mathcal{C} \in \mathfrak{C}$ into four cells⁴ (see figure 4). The mesh \mathcal{M}_{i+1} is constructed by another subdivision of the smaller cells on \mathfrak{C} in \mathcal{M}_i . The meshes \mathbb{M} that are constructed in the described way are called *geometric meshes* [19]. One could refine some cells around hanging nodes to obtain conforming meshes, however we decide to rather treat FE spaces with the up-coming non-conforming meshes than to introduce new cells (see mesh in Fig. 4).

The mesh is stored hierarchically, i.e. the cells and edges know their children. This *parent-child-relationship* permits use to decide, whether an edge or a node is hanging or not [34]. An edge is found to be hanging when itself as well as its ancestor are belonging to a lowest level cell. A node is hanging if it belongs to hanging edges only.

3.2. FE spaces with periodic boundary conditions

The FE space is based on elements, each consisting of a lowest level cell and shape functions, which are defined as tensor-products of polynomials on the reference element and then mapped to the cell. We use shape functions based

⁴ Our code is able to refine towards edges by subdivision of neighbouring cells into two cells [34]. Resolving material edges would be interesting as well, also with anisotropic polynomial degree. This however is beyond the scope of this article.




Fig. 4. The mesh is refined towards the interface corners, while the polynomial order increases linearly away from material corners. In this example the mesh is 2-irregular, however we can cope with arbitrarily irregular meshes.

on Jacobi polynomials [19], which are scaled integrated Legendre polynomials. They can be computed by a recursion formula for any polynomial order. Besides the full tensor-product in each cell, we heavily make use of a linearly truncated set, i.e. only internal basis functions, whose sum of the polynomial degrees in the two coordinate directions is at most $p+1$, are included. For the resulting trunk spaces, also called serendipity spaces, theoretical investigations [19] predict the same convergence results for hp -FEM as for full tensor-product spaces on parallelogram meshes. This is easy to show for meshes with curved elements as well, since one can always find a subspace of full tensor-product elements, which shows exponential convergence as in (12). Our numerical results verify the same (see Section 4).

For a particular adaptively refined mesh \mathcal{M} we define a distribution of polynomial orders for the lowest level cells, e.g. see Figure 4. In [34] it is described how the high order basis functions are determined for a given irregular mesh and polynomial order distribution.

Since we can cope with arbitrarily irregular meshes and arbitrary distributions of polynomial orders, we are able to use different a-priori and a-posteri refinement strategies. Nevertheless, in the present work we analysed an a-priori refinement strategy.

Algorithm 3.1 (A-priori hp -refinement to corners)

- The regular coarse mesh – with topological identification of opposite edges – is equipped with a uniform polynomial degree p .*
- The material corners \mathcal{C} are marked.*
- For $i = 1, \dots, L$ (L the number of refinements)*
 - Loop over all lowest-level cells c of the mesh*
 - If a material corner belongs to the cell c , subdivide it. The children cells take over the polynomial degree.*
 - Otherwise increase the polynomial degree of the cell c .*

Algorithm 3.1 constructs a periodic space with minimal polynomial order p in the tiny cells adjacent to the marked material corners and maximal polynomial order $p + L - 1$ or $p + L$, depending on whether all cells in the coarse mesh touch the material corners or not. The mesh is refined geometrically towards the material corners and becomes 1-irregular, and the polynomial degree increases linearly away from the material corners. In the next section we explain how to construct quasi-periodic spaces and then in section 4 we compare the eigenvalue convergence i.a. for different initial polynomial degrees.

3.3. FE spaces with quasi-periodic boundary conditions

Until now we have constructed the periodic hp -adaptive spaces $\mathcal{S}_0^{p,1}(\Omega, \mathcal{M})$. The basis function identified with the corner π of Ω and these identified with a vertex or an edge on the sides γ_1 or γ_2 , will be changed to fulfil the quasi-periodic boundary conditions (8). In other words, to each periodic basis function $b(\mathbf{x})$ we assign an appropriate quasi-periodic one, $b^{\mathbf{k}}(\mathbf{x})$ for each \mathbf{k} . For basis functions in the interior of Ω , where $b^{\mathbf{k}}|_{\partial\Omega} = 0$, quasi-periodic boundary conditions are trivially fulfilled, and, for all \mathbf{k} they coincide with the periodic counterpart.

In the following we derive the quasi-periodic functions $b^{\mathbf{k}}(\mathbf{x})$. For this we additionally have to distinguish between topologically identical but geometrically different corners and sides. For notations we refer to Fig. 3.

3.3.1. Definition of the Quasi-Periodic Basis Functions

First, we decompose the set of support cells $\mathbb{K}(b)$ for each basis function $b(\mathbf{x})$ in the periodic space $\mathcal{S}_0^{p,1}(\Omega, \mathcal{M})$ into the four subsets⁵

$$\begin{aligned}\mathbb{K}_3(b) &:= \{K \in \mathbb{K}(b) : b(\overline{K} \cap \Pi_2) > 0\}, \\ \mathbb{K}_2(b) &:= \{K \in \mathbb{K}(b) : \exists \mathbf{x} \in \overline{K} \cap \Gamma_2 : b(\mathbf{x}) > 0\}, \\ \mathbb{K}_1(b) &:= \{K \in \mathbb{K}(b) : \exists \mathbf{x} \in \overline{K} \cap \Gamma_1 : b(\mathbf{x}) > 0\}, \\ \mathbb{K}_0(b) &:= \mathbb{K}(b) \setminus (\mathbb{K}_1(b) \cup \mathbb{K}_2(b) \cup \mathbb{K}_3(b)),\end{aligned}$$

and $b(\mathbf{x})$ itself into the functions $b^0(\mathbf{x}), \dots, b^3(\mathbf{x})$ (see Fig. 5) with

$$b^i(\mathbf{x}) := \begin{cases} b(\mathbf{x}) & \text{in } \mathbb{K}_i(b) \\ 0 & \text{otherwise.} \end{cases}$$

In Figure 5 this decomposition is shown. A basis function identified with the (topological) corner π of Ω has got four support cells, each adjacent to a corner Π_i , and coincides with $\mathbb{K}_i(b)$. Thus, the four functions $b^i(\mathbf{x})$ represent the parts of $b(\mathbf{x})$ belonging to one of the four support cells, respectively. A basis function identified with a (topological) side, let it be γ_1 , has support cells⁶ on Γ_1 and Γ_3 , $b^0(\mathbf{x})$ and

⁵ This is possible if the mesh has at least two cells in each direction, which we “trivially” assume from now on.

⁶ One on each side for basis functions identified with an edge, and two for those identified with a vertex.




Fig. 5. In the *top line* we see the basis function identified with the corner π and its representation by functions belonging to one factor area. A basis function on the side γ_2 is shown in the *middle line*. These basis functions are cut into two parts, whereas basis functions in the interior Ω (*bottom line*) fully belong to one factor area.

$b^1(\mathbf{x})$ are the parts of $b(\mathbf{x})$ in these cells, respectively, the other functions $b^2(\mathbf{x})$ and $b^3(\mathbf{x})$ are zero. A basis function in the interior of Ω is cut into only one piece, namely $b^0(\mathbf{x})$. The other functions $b^1(\mathbf{x}), \dots, b^3(\mathbf{x})$ are zero.

Now, the functions

$$b^{\mathbf{k}}(\mathbf{x}) := b^0(\mathbf{x}) + e^{i\mathbf{k}\cdot\mathbf{a}_1}b^1(\mathbf{x}) + e^{i\mathbf{k}\cdot\mathbf{a}_2}b^2(\mathbf{x}) + e^{i\mathbf{k}\cdot(\mathbf{a}_1+\mathbf{a}_2)}b^3(\mathbf{x})$$

meet the quasi-periodicity conditions. The span of these functions defines the space $\mathcal{S}_{\mathbf{k}}^{\mathbf{P},1}(\Omega, \mathcal{M})$.

With the definition of the following factors

$$\phi_{\mathbf{k}}^0 := 1, \quad \phi_{\mathbf{k}}^1 := e^{i\mathbf{k}\cdot\mathbf{a}_1}, \quad \phi_{\mathbf{k}}^2 := e^{i\mathbf{k}\cdot\mathbf{a}_2}, \quad \phi_{\mathbf{k}}^3 := e^{i\mathbf{k}\cdot(\mathbf{a}_1+\mathbf{a}_2)},$$

we can write the quasi-periodic basis functions conveniently as

$$b^{\mathbf{k}}(\mathbf{x}) := \sum_n \phi_{\mathbf{k}}^n b^n(\mathbf{x}). \quad (13)$$

3.3.2. Algorithmic Construction of the subsets \mathbb{K}_i

In the following we present an algorithm to construct the subsets \mathbb{K}_i . For each cell we need to decide, whether its interior shape functions, which edge shape functions and which vertex shape functions are elements of \mathbb{K}_i . We will introduce an algorithm which is based on topological information and attribute sets only, i.e. independent of geometrical information. Vertices and edges, as well as cells are equipped with attributes, which are i.a. used for definitions of different material properties, boundary conditions or refinement strategies. By refining the mesh, these attributes are inherited by the children objects. Since opposite edges, opposite vertices and the four corners are topologically identical (see Fig. 3), they have the same attribute and we cannot decide by means of these attributes to which side of Ω they belong. Thus, we additionally make use of cell attributes.

We need four attribute sets $\mathcal{A}_1, \dots, \mathcal{A}_4$ for cells, two sets \mathcal{E}_1 and \mathcal{E}_2 for the edges and vertices on the sides of the parallelogram and \mathcal{P} for the corner⁷. The intersection of




Fig. 6. Here we show the necessary vertex, edge and cell attributes to determine the subsets \mathbb{K}_i . The shading of the cells corresponds to the attribute sets $\mathcal{A}_1, \dots, \mathcal{A}_4$. Note that the refining algorithm passes attributes from parent to child cells and edges. The middle cell gets a different dielectrical constant and so a distinct attribute.

all these sets must be empty. In Fig. 6 there is an example of a mesh, already refined, with attribute sets $\mathcal{A}_1 = \{1, 10\}$, $\mathcal{A}_2 = \{2\}$, $\mathcal{A}_3 = \{3\}$, $\mathcal{A}_4 = \{4\}$ for the cells, $\mathcal{E}_1 = \{21\}$ and $\mathcal{E}_2 = \{22\}$ for the outer edges and $\mathcal{P} = \{30\}$ for the corners. We might have different material properties in the middle cell, therefore we assigned the additional attribute 10 to it and put it into \mathcal{A}_1 . Furthermore, no vertex on the sides, like the marked one in Fig. 6, has an attribute.

By default all the degrees of freedom in a cell are active. To change that we use

```
CellCondition(CellAttribute,
              Tag(AttributeName1, AttributeName2, ...)).
```

The tags can take the values `SWITCH_OFF`, `SWITCH_ON` or `INACTIVE`. Saying `SWITCH_OFF` only the degrees of freedom

⁷ We have to make sure that cells which topologically share edges or vertices have different attributes.

on the topological entities with specified attributes are inactive. `SWITCH_ON` means that we activate exactly the degrees of freedom specified in the attribute list. With `INACTIVE` we make all the degrees of freedom within the specified cell inactive. E.g.

`CellCondition(\mathcal{A}_2 , SWITCH_OFF($\mathcal{P}, \mathcal{E}_1$))`

means, that in the cells with an attribute in \mathcal{A}_2 all degrees of freedom except those on the entities with attributes in \mathcal{P} or \mathcal{E}_1 are built.

The subsets \mathbb{K}_i of the basis functions are determined by the following list:

- $\mathbb{K}_0: \{ \text{CellCondition}(\mathcal{A}_2, \text{SWITCH_OFF}(\mathcal{P}, \mathcal{E}_1)),$
 $\quad \text{CellCondition}(\mathcal{A}_3, \text{SWITCH_OFF}(\mathcal{P}, \mathcal{E}_1, \mathcal{E}_2)),$
 $\quad \text{CellCondition}(\mathcal{A}_4, \text{SWITCH_OFF}(\mathcal{P}, \mathcal{E}_1)) \}$
- $\mathbb{K}_1: \{ \text{CellCondition}(\mathcal{A}_4, \text{SWITCH_ON}(\mathcal{P}, \mathcal{E}_1)),$
 $\quad \text{CellCondition}(\mathcal{A}_3, \text{SWITCH_ON}(\mathcal{E}_1)),$
 $\quad \text{CellCondition}(\mathcal{A}_1, \mathcal{A}_2, \text{INACTIVE}) \}$
- $\mathbb{K}_2: \{ \text{CellCondition}(\mathcal{A}_2, \text{SWITCH_ON}(\mathcal{P}, \mathcal{E}_2)),$
 $\quad \text{CellCondition}(\mathcal{A}_3, \text{SWITCH_ON}(\mathcal{E}_2)),$
 $\quad \text{CellCondition}(\mathcal{A}_1, \mathcal{A}_4, \text{INACTIVE}) \}$
- $\mathbb{K}_3: \{ \text{CellCondition}(\mathcal{A}_3, \text{SWITCH_ON}(\mathcal{P})),$
 $\quad \text{CellCondition}(\mathcal{A}_1, \mathcal{A}_2, \mathcal{A}_4, \text{INACTIVE}) \}$

Normally, most of the vertices do not have any attribute, in particular vertices created by subdivision of an edge (e.g. the vertex marked with a black circle in figure 6) do not have attributes. To decide if such a vertex without an attribute is located on a side of the domain, we consult the related edges, i.e. the edges to which the vertex belongs. We distinguish three cases:

- The vertex has its own attribute: it is treated according to that attribute.
- The vertex has no own attribute and only one related edge has an attribute: the vertex is treated as if it would have the attribute of that edge.
- The vertex has no own attribute and the related edges have attributes: the vertex is treated as if it would have the attribute of any one of these edges.

In the example in figure 6 the marked vertex is recognised to be on a vertical side, since two related edges have the attribute 22, which is contained in \mathcal{E}_1 .

3.4. Assembly of the system matrices

For simplicity reasons we do not distinguish between TM and TE modes in this section. With the basis functions of the spaces $\mathcal{S}_k^{p,1}(\Omega, \mathcal{M})$ defined just above, we find the matrix eigenvalue problems of (10)

$$\mathbf{A}^k \mathbf{x}^k = \lambda^k \mathbf{M}^k \mathbf{x}^k$$

with the system matrices

$$\mathbf{A}^k = (\mathbf{a}(b_j^k, b_j^k))_{i,j=1}^N, \quad \mathbf{M}^k = (\mathbf{b}(b_j^k, b_j^k))_{i,j=1}^N, \quad (14)$$

where \mathbf{a} and \mathbf{b} stand for the appropriate inner product for the TM or TE mode, respectively. The eigenvalues are $\lambda^k = (\frac{\omega}{c})^2$. After inserting (13) into (14) we get

$$\mathbf{A}^k = \sum_{m,n=0}^3 \phi_k^m \phi_k^n (\mathbf{a}(b_j^m, b_j^n))_{i,j=1}^N,$$

and with the definition of the matrices

$$\mathbf{A}^{mn} := (\mathbf{a}(b_j^m, b_j^n))_{i,j=1}^N,$$

we write

$$\mathbf{A}^k = \sum_{m,n=0}^3 \phi_k^m \phi_k^n \mathbf{A}^{mn}.$$

Due to the cutting procedure, the computation of the sixteen matrices \mathbf{A}^{mn} is exactly as expensive as the direct computation of \mathbf{A}^0 . The multiplication with the phase factors is negligible compared to the overall cost. Thus, the assembly of an arbitrary number of the system matrices \mathbf{A}^k for different quasi-momenta $\mathbf{k} \in B_{\text{red}}$ has about the same cost as the assembly of the single matrix \mathbf{A}^0 . As basis functions in the interior of Ω are not affected by quasi-periodicity, only a small part of \mathbf{A}^k is affected when changing \mathbf{k} .

The integrals in (11) are computed by numerical Gauss quadrature on each element. The number of quadrature points is adapted to the maximal polynomial degree $p = p(c)$. We use sum factorisation [34] to reduce the integration costs from $O(p^6)$ to $O(p^5)$.

4. Numerical Results

The band structure algorithm is implemented in our object-oriented software package `Concepts` [35,36], written in C++. The meshes use an exact representation of curved edges, which is needed for p -FEM and hp -FEM. In order to reduce the number of degrees of freedom N , we use trunk spaces.

For p -FEM and hp -FEM we analyse the error in dependence of the number of degrees of freedom, which is essentially smaller for trunk spaces. For finding the smallest eigenvalues of the generalised matrix eigenvalue problems we use ARPACK [37], for the LU decomposition the library SuperLU [38].

4.1. Band structures and eigenfunctions

We calculated the band structure of four photonic crystals defined by the pattern of their elementary cells, the cylindrical holes, the dielectric veins (both in Fig. 7), the inversely curved dielectric cylinders and a 9×9 structure of dielectric veins with a periodic defect (both in Fig. 7).

In all cases the elementary cell is the square $\Omega = [0, a]^2$, which is scaled to $\widehat{\Omega} = [0, 1]^2$, for which the Brillouin zone is $\widehat{B} = [0, 2\pi]^2$. Then, the angular frequency ω scales with $1/a$. Hence, it is convenient to look at the non-dimensional quantity $\omega a / 2\pi c = \sqrt{\lambda}/2\pi$, where λ is the eigenvalue of the eigenvalue problem on $\widehat{\Omega}$.

The computed band structures of the four photonic crystals are shown in Figures 8 and 9. We want to emphasise that our algorithm is well suited for dielectric patterns with




Fig. 7. The elementary cell with cylindrical holes (*left*), that with dielectric veins (*inner left*), that with inversely curved dielectric rods (*inner right*) and that with a 9×9 structure of dielectric veins with a periodic defect in the middle (*right*). The white region is air ($\epsilon = 1$), the blue region is a dielectric medium ($\epsilon > 1$).




Fig. 8. Band structure of the crystal with cylindrical holes of diameter $0.95 a$ (*left*) and of the crystal with dielectric veins of thickness $0.1 a$ ($0.05 a$ on both sides). The dielectric medium (dark in figure 7) has $\epsilon = 20$, in the rest of the structure we have $\epsilon = 1$. Solid lines denote TE modes, dashed lines denote the TM modes.






Fig. 9. Band structure of the crystal with inversely curved dielectric rods with radius $0.8 a$ (midpoints on the perpendicular bisectors of the sides) and distance between corners of $0.9 a$ (*left*) and of the crystal with a 9×9 structure of dielectric veins of thickness $0.1 a/9$ (*right*). The dielectric medium (dark in figure 7) has $\epsilon = 20$, in the rest of the structure we have $\epsilon = 1$. Solid lines denote TE modes, dashed lines denote the TM modes.

- discontinuous dielectric constants,
- smooth, curved interfaces,
- straight and curved interfaces with corners,
- structures with small local geometry features.

The refinement strategies will be discussed in section 4.2.

Although the band structure is shown for the symmetry lines of the reduced Brillouin zone only, the whole reduced Brillouin zone can be sampled conveniently, since the assembly of the matrices is done only once.

In addition to the eigenvalues the *hp*-adaptive FE algorithm also computes the eigenfunctions accurately. In Fig-



ure 10 we see the squared amplitude⁸ of the TM and the TE mode of the first band at the M point for the crystal with the perturbed 9×9 dielectric vein structure (see Fig 7).

We have chosen the geometric and dielectric parameters for the crystal with dielectric veins (Fig. 7) the same as in [12,13,24]. In [12,13] separation of variables approaches are applied, whereas in [24] first order FE are used. The com-

⁸ The squared amplitude corresponds to the concept of probability density in quantum electrodynamics.




Fig. 10. Squared amplitude of the first TM eigenfunction $|e_k(\mathbf{x})|^2$ (left) and TE eigenfunction $|h_k(\mathbf{x})|^2$ (right) at the M point of the crystal with a 9×9 structure of dielectric veins of thickness $0.1 a/9$. The dielectric medium (dark in figure 7) has $\varepsilon = 20$, in the rest of the structure we have $\varepsilon = 1$. As the TE eigenvalue is twofold, there is another eigenfunction, which results from an interchange of x_1 and x_2 .

parison of these results to ours computed with p -FEM (see Tab. 1) validates our approach and our implementation. Notice the higher accuracy for the TM mode for the same refinement level due to weaker singularities at the interface corners. We present further convergence results in section 4.2.

4.2. Convergence of eigenvalues

Now, we investigate the convergence of the eigenvalues for different refinement strategies, starting with p -refinement. We choose the midpoint between Γ and X , which we name k_c . This is not a particularly “good” or “bad” one.

In Figure 11 the convergence of the smallest eigenvalue is shown for the crystals with cylindrical holes, with dielectric veins and with inversely curved rods (Fig. 7) – for the TM and the TE mode, computed with p -FEM. For the cylindrical holes with only smooth material interfaces we observe exponential convergence in the number of degrees of freedom N as $\exp(-\beta N^{1/3})$ as we expected from hp -theory [31,32,19]. For the crystals with dielectric veins and with inversely curved rods corner interfaces are present and the slope is less steep than for the crystal with cylindrical holes. Due to the smaller inward angle of the dielectric medium at the interface corners the singularity for the inversely curved rods is larger than for the dielectric veins [29], such that we observe a weaker convergence of the eigenvalues.

In Figure 11 the eigenvalues of the crystal with the dielectric veins and the inversely curved rods seem to converge exponentially for p -FEM, although interface corners are present. Nevertheless, if we continue with the p refinement (in Fig. 12 for dielectric veins up to $p = 38$), merely algebraic convergence emerges⁹.

In the following we investigate the convergence of the eigenvalues for geometric refinement – described in section 2.5 – in comparison to p -FEM. In Figure 12 the relative

error of the smallest eigenvalue for the crystal with dielectric veins (Fig. 7) with thickness $0.4a$ and $\varepsilon = 8.9$ is shown. Starting with a coarse mesh with nine cells and $p = 1$ in all cells, hp -FEM shows exponential convergence in contrast to p -FEM, both for the TE and the TM mode. However, in the beginning the polynomial refinement performs better (up to $N \sim 4000$ for the TM mode, up to $N \sim 2000$ for the TE mode). Therefore we investigated the influence of the polynomial order in the coarse mesh for hp -FEM. The results in Figure 12 show, that an initial polynomial order of $p = 2$ performs better than one of order $p = 1$ for all N , and that $p = 4$ performs even better in the beginning, but converges with flatter slope. This behaviour is due to the weak singularities for the used material parameters. Note that the strategy reduces the relative error at about 8000 dof for the TM mode to the order of 10^{-14} , but for the TE mode only to the order of 10^{-6} . In Figure 12 we additionally show the relative error using full tensor-product spaces. Clearly the slopes of these curves for TE and TM mode are not as steep as the ones using trunk spaces. Both methods show exponential convergence as in (12), however with full tensor-product spaces the constant β is worse.

Table 2 shows the numerical TE eigenvalues for the setting just described (as in the left diagram in Fig. 12) for hp -FEM with initial polynomial order¹⁰ $p = 2$, for p -FEM, and pure h -refinement ($p = 1$). h -FEM also converges algebraically, but more slowly than p -FEM. At h -FEM-level 6 ($N = 9216$) only three digits of the eigenvalue are exact, while with p -FEM at $N = 6345$ five digits are exact and with the described hp -FEM-strategy at $N = 6764$ (level 11) there are already six exact digits. With extrapolation of the hp -FEM-values we get 0.4914752, which we take for exact up to 7 digits (one more).

Finally, we analyse the convergence behaviour for a crystal with curved dielectric veins (the third crystal in figure 7), where we even chose an artificially high dielectric contrast (100 : 1), to have an example with a very strong sin-

⁹ With large convergence rate.

¹⁰ More exactly, geometric refinement starts after a first p -refinement step.

Band No.	TM spectrum		TE spectrum		
	lower bound	upper bound	lower bound	upper bound	
1	0	2.22	0	3.73	from [12]
	0	2.31	0	3.73	from [13]
	0	2.312	0	3.743	from [24]
	0	2.30429(73)	0	3.719(34)	p -FEM
2	2.64	5.09	8.42	13.73	from [12]
	2.64	5.09	8.43	13.76	from [13]
	2.650	5.099	8.440	13.704	from [24]
	2.642854(92)	5.0873131(35)	8.40(47)	13.678(20)	p -FEM
3	3.44	5.65	11.01	16.77	from [12]
	3.43	5.91	11.04	16.77	from [13]
	3.454	5.904	11.027	16.785	from [24]
	3.4379333(62)	5.888(50)	10.972(25)	16.741(72)	p -FEM

Table 1

The table shows our results for the relative eigenvalues $\hat{\lambda} = \omega^2 a^2 / c^2$ at the lower and upper bound of the first three bands for the dielectric veins (Fig. 7) in comparison to [12], [13], [24]. We use a polynomial refinement strategy with 9 cells and uniform polynomial order $p = 15$ (963 degrees of freedom). The results of [24] are converted with their given accuracy.




Fig. 11. The convergence of the relative error of the smallest TM (*left*) and TE eigenvalue (*right*) at k_c for the crystals with cylindrical holes, with dielectric veins and with inversely curved rods (Fig. 7, same geometric and dielectric parameters as in Fig. 8 and Fig. 9 (*left*)). The computations were done with p -FEM.

gularity in the TE mode. We chose $\varepsilon = 100$ in the dark region of figure 7 and $\varepsilon = 1$ in the rest of the structure. The distance between the corners is $0.6a$, the curvature is determined by circles with radius $0.8a$ and midpoints on the perpendicular bisectors of the sides. The results of the computations with the same refinement strategies as in the previous example (see figure 12) are shown in figure 13. For the TE mode the convergence is much slower and hp -FEM clearly beats polynomial refinement, already at an accuracy of 10^{-3} . Note that in figure 13 we have a relative error of 10^{-5} (TE) at $N = 8000$ in comparison to 10^{-7} in figure 12. The worse convergence in the TE mode points to the

stronger singularity due to the increased contrast and the outer angle which is larger due to the curved edges. The polynomial refinement for the TM mode is most efficient up to a relative error bound around 10^{-12} , then hp -FEM with initial polynomial degrees of 2 and 4 takes over.

5. Conclusion

We introduced an algorithm based on hp finite elements with hanging nodes for computing the photonic crystal band structure. We showed that the eigenvalues converge exponentially for smooth and polygonal interfaces. In ex-




Fig. 12. Convergence of the relative error of the first eigenvalue at k_c for the TM-mode (*left*) and TE mode (*right*) of the crystal with dielectric veins ($\varepsilon = 8.9$ in the veins, $\varepsilon = 1$ in the middle, vein thickness 0.2 at each side). We use *p*-FEM and *hp*-FEM, the latter with different initial polynomial degree.




Fig. 13. Convergence of the relative error of the first eigenvalue at k_c for the TM-mode (*left*) and TE mode (*right*) of the crystal with curved dielectric veins (the third crystal in figure 7). We use $\varepsilon = 100$ in the white region and $\varepsilon = 1$ in the rest. The distance between the corners is $0.6a$, the circles used for the veins have radius $0.8a$, their midpoints lie on the perpendicular bisectors of the sides. We use *p*-FEM and *hp*-FEM, the latter with different initial polynomial degree.

amples with polygonal interfaces we observed faster convergence with pure polynomial enrichment (*p*-FEM) for the first refinement levels than with *hp*-FEM – both for the TM and the TE mode. This is due to the relatively weak singularities. Nevertheless to achieve very high accuracies, *hp*-FEM is by far more efficient than *p*-FEM, especially when the singularities are stronger. The discretisation error of pure cell refinement (*h*-FEM) shows much slower convergence. These results meet the expectations from *hp*-FEM theory.

The presented algorithm is able to compute the band structure for polygonally shaped elementary cells to high accuracy at low computational costs. This is due to the ex-

ponential convergence of *hp*-FEM and because the system matrices are assembled only once for the whole Brillouin zone.

To extend the idea of the presented algorithm to 3D photonic crystals one could use *hp*-adaptive nodal elements with weighted regularisation [39] or *hp*-adaptive edge elements [40,20].

6. Acknowledgement

The authors would like to thank Prof. R. Hiptmair, Prof. Ch. Schwab (both ETH Zürich, Switzerland) and Prof. M. Dauge (Université de Rennes 1, France) for their sup-

level	<i>h</i> -FEM		<i>p</i> -FEM		<i>hp</i> -FEM	
	#dof	$\frac{\omega_{TE,0}a}{2\pi c}$	#dof	$\frac{\omega_{TE,0}a}{2\pi c}$	#dof	$\frac{\omega_{TE,0}a}{2\pi c}$
1	9	0.521302619112	9	0.521302619112	9	0.521302619112
2	36	0.501735291198	27	0.497095810781	27	0.497095810781
3	144	0.494952283861	45	0.495570239622	108	0.493365508380
4	576	0.492664756896	72	0.493837964737	268	0.492231220419
5	2304	0.491885702189	108	0.492751880410	512	0.491725406461
6	9216	0.491618020101	153	0.492340949399	904	0.491563775139
7			207	0.491998065356	1492	0.491506786403
8			270	0.491855851430	2324	0.491486485296
9			342	0.491735848233	3448	0.491479231178
10			423	0.491681227299	4912	0.491476634000
11			513	0.491624540578	6764	0.491475702552
12			612	0.491597555930	9052	0.491475368251
13			720	0.491568698587	11824	0.491475248235
14			837	0.491554083965		
15			963	0.491537578751		
18			1395	0.491513511149		
23			2295	0.491493587640		
28			3420	0.491485836966		
33			4770	0.491481669113		
38			6345	0.491479554612		

Table 2

Convergence of the first eigenvalue for the TE mode for the crystal with dielectric veins (see Fig. 7, $\varepsilon = 8.9$, vein thickness 0.2 at each side) at $\mathbf{k} = (1/2a, 0)$ for pure mesh refinement (*h*-FEM), pure polynomial order enlargement (*p*-FEM) and adaptive *hp*-FEM. For *p*-FEM and *hp*-FEM the level corresponds to the maximal polynomial degree in the discrete space. With *hp*-FEM we first refine only the polynomial degree and start then with geometric mesh refinement towards the four interface corners. With extrapolation (exponential ansatz) we expect $\omega_{TE,0}a/2\pi c \approx 0.4914752$.

port and assistance.

References

- [1] J. D. Joannopoulos, R. D. Meade, and J. N. Winn. *Photonic Crystals: Molding the Flow of Light*. 1995.
- [2] Eli Yablonovitch. Inhibited spontaneous emission in solid-state physics and electronics. *Phys. Rev. Lett.*, 58(20):2059–2062, May 1987.
- [3] Peter Kuchment. *Floquet Theory for Partial Differential Equations*. Birkhäuser Verlag, Basel, 1993.
- [4] K. Busch. Photonic band structure theory: assessment and perspectives. *Compte Rendus Physique* 3, 53–66, 3(53):53–66, 2002.
- [5] Robert D. Meade, Karl D. Brommer, Andrew M. Rappe, and J. D. Joannopoulos. Existence of a photonic band gap in two dimensions. *Appl. Phys. Lett.*, 61(4):495–497, Jul 1992.
- [6] R.D. Meade, A.M. Rappe, K.D. Brommer, J.D. Joannopoulos, and O.L. Alerhand. Accurate theoretical-analysis of photonic band-gap materials. *Physical Review B*, 48(11):8434–8437, Sep 1993.
- [7] Steven G. Johnson and J. D. Joannopoulos. Block-iterative frequency-domain methods for maxwell’s equations in a planewave basis. *Optics Express*, 8(3):173–190, Jan 2001.
- [8] K. M. Leung and Y. Qiu. Multiple-scattering calculation of the two-dimensional photonic band structure. *Phys. Rev. B*, 48(11):7767–7771, Sep 1993.
- [9] Kazuo Ohtaka, Tsuyoshi Ueta, and Katsuki Amemiya. Calculation of photonic bands using vector cylindrical waves and reflectivity of light for an array of dielectric rods. *Phys. Rev. B*, 57(4):2550–2568, Jan 1998.
- [10] W. C. Sailor, F. M. Mueller, and Pierre R. Villeneuve. Augmented-plane-wave method for photonic band-gap materials. *Phys. Rev. B*, 57(15):8819–8822, Apr 1998.
- [11] Esteban Moreno, Daniel Erni, and Christian Hafner. Band structure computations of metallic photonic crystals with the multiple multipole method. *Phys. Rev. B*, 65(15):155120, Apr 2002.
- [12] Alexander Figotin and Yuri A. Godin. The computation of spectra of some 2D photonic crystals. *Journal of computational physics*, 136:585–598, 1997.
- [13] Igor Ponomarev. Separation of variables in the computation of spectra in 2-D photonic crystals. *SIAM Journal on Applied Mathematics*, 61(4):1202–1218, 2001.
- [14] J. B. Pendry and A. MacKinnon. Calculation of photon dispersion relations. *Phys. Rev. Lett.*, 69(19):2772–2775, Nov 1992.
- [15] C. T. Chan, Q. L. Yu, and K. M. Ho. Order-n spectral method for electromagnetic waves. *Phys. Rev. B*, 51(23):16635–16642, Jun 1995.
- [16] Kazuaki Sakoda and Jun Kawamata. Novel approach to photonic bands with frequency-dependent dielectric constants. *Optics Express*, 3(1):12–18, July 1998.
- [17] Dietrich Braess. *Finite Elemente*. Springer, Berlin, 2003.
- [18] Barna Szabo and Ivo Babuska. *Finite Element Analysis*. John Wiley and Sons, New York, 1991.
- [19] Christoph Schwab. *p- and hp- Finite Element Methods: Theory and Applications in Solid and Fluid Mechanics*. Oxford University Press, 1998.
- [20] Leszek Demkowicz. *Computing with HP-Adaptive Finite Elements: One and Two Dimensional Elliptic and Maxwell Problems*. Chapman and Hall / CRC Applied Mathematics and Nonlinear Science, 2006.
- [21] I. Babuska and B. Q. Guo. The h-p version of the finite-element method for domains with curved boundaries. *Siam J. On Numerical Analysis*, 25:837–861, 1988.
- [22] M. Ainsworth and B. Senior. An adaptive refinement strategy for hp-finite element computations. *Appl. Numerical Mathematics*, 26:165–178, 1998.
- [23] W. Dörfler and V. Heuveline. Convergence of an adaptive hp finite element strategy in one space dimension. *Applied Numerical Mathematics*, 57(10):1108–1124, Oct 2007.
- [24] Waldemar Axmann and Peter Kuchment. An efficient finite element method for computing spectra of photonic and acoustic band-gap materials i. scalar case. *Journal of Computational Physics*, 150:468–481, 1999.
- [25] David C. Dobson. An Efficient Method for Band Structure Calculations in 2D Photonic Crystals. *Journal of Computational Physics*, 149(2):363–376, March 1999.
- [26] David C. Dobson, Jayadeep Gopalakrishnan, and Joseph E. Pasciak. An efficient method for band structure calculations in 3d photonic crystals. *Journal of Computational Physics*, 161(2):668–679, July 2000.
- [27] Daniele Boffi, Matteo Conforti, and Lucia Gastaldi. Modified edge finite elements for photonic crystals. *Numerische Mathematik*, 105(2):249–266, Dec 2006.
- [28] Charles Kittel. *Introduction to Solid State Physics*. John Wiley and Sons, New York, 2004.
- [29] Martin Petzold. *Regularity and error estimates for elliptic problems with discontinuous coefficients*. PhD thesis, FU Berlin, Berlin, Jan 2001.
- [30] M. Costabel, M. Dauge, and S. Nicaise. Singularities of Maxwell interface problems. *Rairo-mathematical Modelling Numerical Analysis-modélisation Mathématique Et Analyse Numérique*, 33(3):627–649, 1999.

- [31] I. Babuška, B. Q. Guo, and J. E. Osborn. Regularity and numerical solution of eigenvalue problems with piecewise analytic data. *SIAM J. Numer. Anal.*, 26(6):1534–1560, 1989.
- [32] Ben Qi Guo and Hae Soo Oh. The h - p version of the finite element method for problems with interfaces. *Internat. J. Numer. Methods Engrg.*, 37(10):1741–1762, 1994.
- [33] George Em Karniadakis and Spencer J. Sherwin. *Spectral/hp Element Methods for Computational Fluid Dynamics*. Oxford University Press, Oxford, 1999.
- [34] Philipp Frauenfelder. *hp-Finite Element Methods on Anisotropically, Locally Refined Meshes in Three Dimensions with Stochastic Data*. PhD thesis, ETH Zürich, Zürich, 2004.
- [35] Philipp Frauenfelder and Christian Lage. Concepts – An Object-Oriented Software Package for Partial Differential Equations. *Mathematical Modelling and Numerical Analysis*, 36(5):937–951, September 2002.
- [36] Concepts Development Team. Concepts homepage. <http://www.concepts.math.ethz.ch>, 2008.
- [37] R.B. Lehoucq, D.C. Sorensen, P.A. Vu, and C. Yang. Arpack: Fortran subroutines for solving large scale eigenvalue problems.
- [38] James W. Demmel, Stanley C. Eisenstat, John R. Gilbert, Xiaoye S. Li, and Joseph W. H. Liu. A supernodal approach to sparse partial pivoting. *SIAM J. Matrix Analysis and Applications*, 20(3):720–755, 1999.
- [39] Martin Costabel, Monique Dauge, and Christoph Schwab. Exponential convergence of hp -FEM for Maxwell’s equations with weighted regularization in polygonal domains. *Mathematical Models and Methods in Applied Sciences*, 15(4):575–622, April 2005.
- [40] Mark Ainsworth, Joe Coyle, Paul D. Ledger, and Ken Morgan. Computing Maxwell eigenvalues by using higher order edge elements in three dimensions. *IEEE Transactions on Magnetics*, 39(5):2149 – 2153, 2003.